



NITECH®

77205D-PS

High Profile Semi-Automatic Stretch Wrapper with 200% Powered Pre-Stretch

OVERVIEW

If your looking for a heavy-duty, low maintenance stretch wrapper the Powered pre-stretch 77 series is the answer. With this easy to operate machine you load the 48" variable speed turntable, attach the wrap to the load, select a program, press start and walk away. The carriage raises and wraps the load until the photo electric eye senses the top of the load. When the top of the load is sensed a preset number of top wraps are applied. After the number of top wraps the film carriage then reverses itself and continues to wrap the load as it lowers. When it reaches the bottom the turntable stops in the same position that it started for easy unloading. The no-thread powered pre-stretch offers excellent load containment and the best in film savings.

SPECIFICATIONS

Maximum Load Size:	52" x 52" x 80" (120" Mast Height Available)
Production Capacity:	40 loads per hour
Machine Dimensions:	111"L x 48"W x 83"H
Weight Capacity:	4,000 LB.
Electrical Data:	120 VAC 60 Hertz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	48" round steel diamond deck or 48" octagon steel diamond deck w/5" skirt
Turntable Height:	14 5/8"
Turntable Drive:	3/4 hp DC motor (totally enclosed fan cooled). Variable speed turntable 0-15 RPM with soft start and soft stop Lubrication free enclosed gear drive design Synthetic lube in all gearboxes (-30 to 120 Degrees) Turntable indexing home alignment
Controls:	PLC-Programmable Logic Control with pre-programmed sequences Turntable Variable Speed Dial Dispenser Variable Speed Dial Film Tension Variable Dial Turntable Jog Emergency Stop Button Photo Eye for Automatic Load Height Sensing On/Pause Button Start/Resume Switch 3 Indicator Light, Power, Ready, and Tension Liquid Crystal Display



Film Delivery:	No-Thread Powered Pre-Stretch Stretch Level 200% fixed (gear switch to 250% or 300%) Force to Load dial for different load weights Accepts 12" to 20" Rolls of Stretch Film 1/2 hp DC 90 Volt Motor
Film Carriage:	Variable Speed Carriage 0-20 FPM 1/4 HP 90 Volt DC Motor Dispenser Kill Switch Top / Bottom Top Over Wrap
Tower Construction:	Formed All Steel Tower 80" Wrap Height (Optional Wrap Height Available) #40 Chain Drive Lift UHMW Full Tower Slides
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Easy Access to all Components Forklift Portable from Front or Rear
Warranty:	3 year limited warranty (100% of all components).
Shipping Weight:	1,340 lb.

NITECH
911 23rd St. East
Columbus, NE. 68602-1023

1-800-397-1100

Ph: 402-563-3188
Fax: 402-563-2792
nitechindustries.com