



# NITECH®

## 77205D-RBM Turn-n-Wrap High Profile semi-automatic stretch wrapper with Magnetic Particle Brake Roller.

### OVERVIEW

If your looking for a heavy-duty, high volume, low maintenance stretch wrapper using netting or film application the RBM unit is the answer. With this easy to operate machine you load the 48" variable speed turntable, attach the wrap to the load, hit the switch and walk away. The carriage raises and wraps the load until the photo electric eye sense the top of the load. When the top of the load is sensed a preset number of wraps are applied. After the number of wraps the film carriage then reverses itself and continues to wrap the load as it lowers. When it reaches the bottom, the turntable stops in the same position that it started for easy unloading. These machines with their RMB roller brake are designed for netting on those applications where ventilation is critical or can equally operate using the standard films with up to 150% stretch capabilities.

### SPECIFICATIONS

Maximum Load Size:	56" x 56" x 74"
Production Capacity:	40 loads per hour
Machine Dimensions:	101"L x 48"W x 83"H
Weight Capacity:	4,000 LB.
Electrical Data:	120 VAC 60 Hertz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	48" Round Steel Diamond Deck
Turntable Height:	14 5/8"
Turntable Drive:	3/4 hp DC Motor (Totally Enclosed Fan Cooled) Variable Speed Turntable 0-15 RPM with Soft Start and Soft Stop Enclosed Gear Drive Design Synthetic Lube in all Gearboxes (-30-120°F) Turntable Indexing Home Alignment
Controls:	PLC-Programmable Logic Control with pre-programmed sequences Turntable Variable Speed Dial Dispenser Variable Speed Dial Film Tension Variable Dial Emergency Stop Button Photo Eye for Automatic Load Height Sensing On/Pause Button Start/Resume Switch 3 Indicator Light, Power, Ready, and Tension Liquid Crystal Display



Film Delivery:	RBM-magnetic particle roller brake Uretane roller constant drag Stretch level 150% on film Tension Dial for adjustment Accepts 12-30" rolls of netting or Stretch film 150 ft/lb magnetic particle brake
Film Carriage:	74" Wrap Height (Optional Wrap Height Available) Top Over Wrap Variable Speed Carriage 0-20 FPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports Dispenser Kill Switch Top/Bottom
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Easy Access to all Components Forklift Portable from Front and Rear
Warranty:	3 Year Limited Warranty
Shipping Weight:	1,125 lb.

NITECH  
911 23rd St. East  
Columbus, NE. 68602-1023

## 1-800-397-1100

Ph: 402-563-3188  
Fax: 402-563-2792  
nitechindustries.com